

## Marine 2T DFI Motor Oil

### Description

Semi-synthetic, ultra-high-performance 2-stroke motor oil specially developed for the marine sector. Specially developed to satisfy the complex requirements of the latest generation of direct injection engines. Convinces with maximum corrosion and motor protection and ensures smooth operation in all load conditions. Ensures optimum lubrication even at high operating temperatures, guarantees maximum engine and piston cleanliness and low-fuming combustion.

### Properties

- excellent corrosion protection
- outstanding engine cleanliness
- optimum lubrication under all operating conditions
- for separate and mixture lubrication

### Approvals

NMMA TC-W3®

**LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required**

Evinrude E-Tec Engines • ISO L-EGC • ISO L-EGD • JASO FC • JASO FD • Mercury DFI 2 stroke Engines

### Technical data

Density at 15 °C	0,865 g/cm <sup>3</sup> DIN 51757
Viscosity at 40 °C	37,5 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at 100 °C	7 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity index	150 DIN ISO 2909
Pour point	-39 °C DIN ISO 3016
Flash point	104 °C DIN ISO 2592
Total base number	4,4 mg KOH/g DIN ISO 3771
Color / appearance	red

### Areas of application

Recommended and tested for Evinrude E-Tec and Mercury DFI 2-stroke engines. Can be used in the mixing ratios 1:30, 1:50 or 1:100. Also suitable for all other 2-stroke and DFI 2-stroke engines. For separate and mixture lubrication.



### Comment

Suitable for the mixing ratios:

1:30

1:50

1:100

### Application

As is usual for 2-stroke motor oils for mixed and separate lubrication. The mixing ratios of the individual motor manufacturers are to be observed.

### Available pack sizes

1 l Canister plastic	25088 D-BOOKLET
5 l Canister plastic	25063 D-BOOKLET

**Our information is based on thorough research and may be considered reliable, although not legally binding.**