



THINNERS 17

600/V607/17

DESCRIPTION:

Thinners 17 is a solvent naphtha

RECOMMENDED USE:

Used as a thinner / brushwash for Antifouling,

AVAILABILITY:

1 litre, 2.5 litre

FINISH:

N/A

COLOUR:

Clear thin liquid

TYPICAL S.G. (SPECIFIC GRAVITY):

0.85 @ 20 °C

VOLUME SOLIDS:

N/A

WET FILM THICKNESS W.F.T

N/A

DRY FILM THICKNESS D.F.T

N/A

EXPECTED SPREADING RATE:

N/A

The practical spreading rate may be lower as this depends on factors such as the porosity and roughness of the surface to be painted and material losses during application.

TYPICAL VISCOSITY

N/A

FLASH POINT:

40 °C (closed cup)

DRYING TIME: @ RECOMMENDED D.F.T

Touch dry: N/A

Hard dry: N/A

Full hardness: N/A

Low temperature and high humidity will adversely affect application, drying and performance of any coating.

MINIMUM OVERCOATING TIME:

N/A

APPLICATION SPECIAL CONDITIONS:

N/A

VOC CONTENT:

N/A

VOC's (Volatile Organic Compounds) contribute to atmospheric pollution

APPLICATION DETAILS:

Application N/A
restrictions

Method N/A

Thinner N/A
(Max vol):

Nozzle size: N/A

Nozzle N/A
pressure:

Cleaning N/A
solvent:

Recoat N/A
interval:

SURFACE PREPARATION:

N/A

MIXING INSTRUCTIONS:

N/A

APPLICATION CONDITIONS:

N/A

For further advice contact Teamac Technical Services on +44(0)1482 320194

The physical constants are subject to normal manufacturing tolerances.

"COVERING OUR CUSTOMERS' NEEDS SINCE 1908"

TEAMAC

Lockwood Street, Hull HU2 0HN

Tel.: +44(0)1482 320194. Fax: +44(0)1482 219266

Email: info@teamac.co.uk

www.teamac.co.uk

THINNERS 17**600/V607/17**

PRECEDING COAT:

N/A

SUBSEQUENT COAT:

N/A

REMARKS:

Flamability limits in air:- Lower - 1% by volume
Upper - 7% by volume

Vapour pressure:- 3mm HG @ 20°C

HEALTH AND SAFETY:

See safety data sheet - SDS 10707

ISSUED:

23 October 2009

REVISION:

0

The information given in this data sheet is based on experience and is accurate to the best of our knowledge. No guarantee should be implied, however, since the conditions of use are beyond our control. This data sheet does not constitute a specification. In case of doubt as to the suitability of the product please contact our Technical Service Department on 01482 320194.

For further advice contact Teamac Technical Services on +44(0)1482 320194

The physical constants are subject to normal manufacturing tolerances.

"COVERING OUR CUSTOMERS' NEEDS SINCE 1908"

TEAMAC

Lockwood Street, Hull HU2 0HN

Tel.: +44(0)1482 320194. Fax: +44(0)1482 219266

Email: info@teamac.co.ukwww.teamac.co.uk