

Stain Remover

Boatcare

Suitable for Cleaning of GRP & Painted Surfaces



PRODUCT DESCRIPTION

A high strength penetrating gel that quickly and easily removes stains, such as light rusting and yellowing, on GRP and painted surfaces.

* Reactive formula - no need to scrub surfaces, avoids scratching

* Thick gel consistency - will not run when applied to vertical surfaces

PRODUCT INFORMATION

Colour	YMB822
Specific Gravity	1.02
Volume Solids	11%
Typical Shelf Life	2 yrs
VOC (As Supplied)	552 g/lt
Unit Size	500 ml

DRYING/OVERCOATING INFORMATION

Drying

Overcoating

Substrate Temperature

Overcoated By	5°C (41°F)		10°C (50°F)		23°C (73°F)		35°C (95°F)	
	Min	Max	Min	Max	Min	Max	Min	Max

APPLICATION AND USE

Preparation	To avoid scratches caused by dirt, clean the surface with Super Cleaner and rinse with water before treatment.
Method	Apply Stain Remover generously with a brush, sponge or cloth using circular movements. Leave for 10 minutes, then rinse with fresh water.
Hints	Mixing - Stir or shake thoroughly.
Some Important Points	Product temperature should be minimum 5°C/41°F and maximum 35°C/95°F. Ambient temperature should be minimum 5°C/41°F and maximum 35°C/95°F. Substrate temperature should be minimum 5°C/41°F and maximum 35°C/95°F.
Compatibility/Substrates	Suitable for use on GRP and painted surfaces.
Number of Coats	1
Application Methods	Brush/Cloth/Sponge.

TRANSPORTATION, STORAGE AND SAFETY INFORMATION

Storage	GENERAL INFORMATION: Exposure to air and extremes of temperature should be avoided. For the full shelf life of Stain Remover to be realised ensure that between use the container is firmly closed and the temperature is between 5°C/41°F and 35°C/95°F. Keep out of direct sunlight. TRANSPORTATION: Stain Remover should be kept in securely closed containers during transport and storage.
Safety	GENERAL: Read the label safety section for Health and Safety Information, also available from our Technical Help Line. DISPOSAL: Do not discard tins or pour paint into water courses, use the facilities provided. It is best to allow paints to harden before disposal. Remainders of Stain Remover cannot be disposed of through the municipal waste route or dumped without permit. Disposal of remainders must be arranged for in consultation with the authorities.
IMPORTANT NOTES	<i>The information given in this sheet is not intended to be exhaustive. Any person using the product without first making further written enquiries as to the suitability of the product for the intended purpose does so at their own risk and we can accept no responsibility for the performance of the product or for any loss or damage (other than death or personal injury resulting from negligence) arising out of such use. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.</i>

Please refer to your local representative or visit <http://www.yachtpaint.com> for further information.

All trademarks mentioned in this publication are owned by, or licensed to, the AkzoNobel group of companies. © AkzoNobel 2014.