

Super Cleaner.

Boatcare

Cleaning and degreasing.

PRODUCT DESCRIPTION

Super Cleaner. is a highly concentrated cleaner. Removes wax, oil and contamination effectively. Suitable for hand and high pressure machine washing. Degreases and cleans with no damage to gelcoat or paintwork. Always use before waxing.

- * Very effective degreasing when used at higher concentrations.
- * Easy to use
- * Does not damage acrylic glass
- * Also suitable, when diluted, for general cleaning on the boat, bilge/engine or car
- * Biodegradable.

PRODUCT INFORMATION

Colour	YMB620
Specific Gravity	0.98
Volume Solids	30%
Mix Ratio	Light - medium cleaning - 4 -8 caps to 4 litres water. Heavier cleaning - use undiluted.
Typical Shelf Life	2 yrs
VOC (As Supplied)	0.00 g/lit
Unit Size	500 ml

DRYING/OVERCOATING INFORMATION

Drying

Overcoating Substrate Temperature

Overcoated By	5°C (41°F)		10°C (50°F)		23°C (73°F)		35°C (95°F)	
	Min	Max	Min	Max	Min	Max	Min	Max


APPLICATION AND USE


Preparation	Rinse with fresh water and allow to dry.
Method	Choose appropriate mixing ratio. Add the required number of capfuls of Super Cleaner. to fresh water. Apply Super Cleaner. to a damp cloth or sponge, then wipe the whole surface to be cleaned using moderate pressure. Rinse with fresh water.
Some Important Points	Product temperature should be minimum 5°C/41°F and maximum 35°C/95°F. Ambient temperature should be minimum 5°C/41°F and maximum 35°C/95°F. Substrate temperature should be minimum 5°C/41°F and maximum 35°C/95°F.
Compatibility/Substrates	Suitable for use on GRP, painted and metal surfaces.
Application Methods	Brush/Cloth/Sponge.

TRANSPORTATION, STORAGE AND SAFETY INFORMATION

Storage	GENERAL INFORMATION: Exposure to air and extremes of temperature should be avoided. For the full shelf life of Super Cleaner. to be realised ensure that between use the container is firmly closed and the temperature is between 5°C/40°F and 35°C/95°F. Keep out of direct sunlight. TRANSPORTATION: Super Cleaner. should be kept in securely closed containers during transport and storage.
Safety	GENERAL: Read the label safety section for Health and Safety Information, also available from our Technical Help Line. DISPOSAL: Do not discard tins or pour paint into water courses, use the facilities provided. It is best to allow paints to harden before disposal. Remainders of Super Cleaner. cannot be disposed of through the municipal waste route or dumped without permit. Disposal of remainders must be arranged for in consultation with the authorities.

Please refer to your local representative or visit www.yachtpaint.com for further information.

 International®, the AkzoNobel logo and other products mentioned in this publication are trademarks of, or licensed to Akzo Nobel. ©Akzo Nobel 2009.




Super Cleaner.
Boatcare
Cleaning and degreasing.



IMPORTANT NOTES

The information given in this sheet is not intended to be exhaustive. Any person using the product without first making further written enquiries as to the suitability of the product for the intended purpose does so at their own risk and we can accept no responsibility for the performance of the product or for any loss or damage (other than death or personal or injury resulting from negligence) arising out of such use. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.

Please refer to your local representative or visit www.yachtpaint.com for further information.

 International®, the AkzoNobel logo and other products mentioned in this publication are trademarks of, or licensed to Akzo Nobel. ©Akzo Nobel 2009.

Ref:3575 Issue Date:10/09/2010